

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number  
**WO 2005/019025 A1**

(51) International Patent Classification<sup>7</sup>: **B64B 1/34**

(21) International Application Number:  
PCT/US2003/025458

(22) International Filing Date: 15 August 2003 (15.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant and

(72) Inventor: **NAGY, Imre** [HU/US]; 6454 Cascade Street,  
San Diego, CA 92122 (US).

LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,  
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


**Published:**

— with international search report

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: HIGH SPEED AIRSHIP



(57) Abstract: A high speed airship (10) with multiple inflatable chambers (11) arranged in a multiplicity of tubular clusters to enhance structural strength and to create a centrally located passenger or cargo tunnel (18) to increase passenger safety. A conical shaped rigid frame front cabin (14) attached to the front end of the airship, and a conical shape rigid frame aft cabin (15) attached to the aft end of the airship, designed to reduce aerodynamic drag, to achieve high speed, and to be able to land on water. Specially designed multiple sections with multiple inner tubes to increase safety. Helium recovery system to control balance and buoyancy without the loss of helium and to eliminate the use of ballast, which otherwise would reduce lifting capacity. Independently rotateable propulsion units (22) for rapid balance and buoyancy control in emergency and to provide high maneuverability to eliminate the need of ground crew.

WO 2005/019025 A1